



Z5040A	
Max. Drilling Capacity	40(cast iron)/ 32 (steel) mm
Spindle travel	190mm
Distance spindle axis to column surface	330mm
Max. Distance spindle nose to worktable	630
Max. Distance spindle nose to base	1200mm
Spindle taper	MT.4
Spindle speeds range (rpm)	67-2500r/min
Spindle speeds	12
Dimension of worktable surface	450×390mm
Dimension of base	410×395mm
Overall height	2300mm
Motor	1.5/2.2KW
G.W./N.W.	550/500kg
Ship measurement	1030×645×2170mm



ZX7045 Milling&Drilling Machine

Max. Drilling Capacity	45mm
Width of face milling	80mm
Diameter of vertical milling	28mm
Spindle travel	120mm
Distance spindle axis to column surface	260mm
Max. Distance spindle nose to worktable	475mm
Spindle taper	MT.4
Spindle speeds range(rpm)	65-1380rpm
Spindle speeds	6
Dimension of worktable surface	820×240mm
Travel of worktable	550×200mm
Overall height	1050mm
Motor	1100W6LEVEL
G.W./N.W.	370/320kg
Ship measurement	103×98×123cm



Z5032A

Z5032A	
Max. Drilling Capacity	32mm
Spindle travel	155mm
Distance spindle axis to column surface	330mm
Max. Distance spindle nose to worktable	685mm
Max. Distance spindle nose to base	1260mm
Spindle taper	MT4
Spindle speeds range (rpm)	125-3030rpm
Spindle speeds	12
Dimension of worktable surface	450×390mm
Dimension of base	420×370mm
Overall height	2190mm
Motor	1.1/1.5KW
G.W./N.W.	580/540kg
Ship measurement	920×560×2295mm